

和尔胜产品目录

霍尔种类	产品型号	工作电压	功耗电流	BOP/BRP	输出电流	输出方式	工作温度
全极低功耗	1232	2.7V-5.5V	1.6uA	±30Gs	5mA	TP	-40~85°C
	1233	2.7V-5.5V	1.6uA	±70Gs	5mA	TP	-40~85°C
	1251	1.65V-3.5V	5.0uA	±30Gs	1mA	TP	-40~85°C
	1258	1.7V-5.5V	5.0uA	±30Gs	10mA	OD	-40~85°C
	1262	1.65V-3.5V	5.0uA	±20Gs	5mA	TP	-40~85°C
双极锁存型	2141	4.0V-30V	3.0mA	±60Gs	25mA	OC	-40~150°C
	2163N	3.5V-24V	3.5mA	±30Gs	100mA	OD	-40~150°C
	2173NP	2.5V-26V	3.0mA	±30Gs	25mA	Pull up	-40~150°C
	2178	2.0V-5.5V	9.0uA	±30Gs	10mA	OD	-40~150°C
	2179	2.0V-5.5V	600uA	±30Gs	10mA	OD	-40~150°C
	2180	2.5V-26V	3.0mA	±50Gs	25mA	OD	-40~150°C
	2182	3.0V-24V	3.0mA	±40Gs	50mA	OD	-40~150°C
	2185N	2.5V-26V	3.0mA	±30Gs	25mA	OD	-40~150°C
	2186	3.0V-26V	3.0mA	±30Gs	25mA	OD	-40~150°C
	2188	2.5V-26V	3.0mA	±15Gs	50mA	OD	-40~150°C
	2193P	2.5V-26V	3.0mA	±15Gs	25mA	Pull up	-40~150°C
单极型开关	3143	4.0V-30V	3.5mA	200Gs	25mA	OC	-40~150°C
	3144	3.0V-24V	2.5mA	90Gs	50mA	OD	-40~150°C
线性输出型	449E	3.0V-6.5V	2.5mA	2mV/Gs	10mA	TP	-40~85°C
	449X	2.8V-6.0V	3.3mA	1.5mV-13mV/Gs	5mA	TP	-40~150°C
全极型开关	5271	2.5V-26V	2.5mA	±80Gs	25mA	OD	-40~150°C
	5272	2.5V-26V	2.5mA	±30Gs	25mA	OD	-40~150°C
	5273P	2.5V-26V	2.5mA	±80Gs	25mA	Pull up	-40~150°C
	5274P	2.5V-26V	2.5mA	±30Gs	25mA	Pull up	-40~150°C
	5275	2.5V-26V	2.5mA	±175Gs	25mA	OD	-40~150°C
	5278P	2.5V-26V	2.5mA	±175Gs	25mA	Pull up	-40~150°C